

# **270 MICROSPRINT**

**VOTED 02-05-2026**

If the rule doesn't say you can, the default is you can't, unless approved by the Board of Directors and voted on by the class.

- 1) Drivers must be a minimum of 13 years of age as of date of race.
- 2) Placement of transponders must be 21" behind front axle on right side of car, If one is being used.
- 3) Single Cylinder 2 cycle 250cc motors with a maximum displacement of 270cc.
- 4) 2- stroke 250cc engines- 16.4754 cu.in. (or 270cc) or 450cc 4-stroke stock bore and stroke.
- 5) Carburetors only; 450cc 4- stroke engines may use fuel injection with OEM throttle body, Race fuel allowed.
- 6) Minimum weight 600 lbs.
- 7) Any material used for adding weight must be welded or bolted to the car structure, be painted bright white and labeled with the race car number.
- 8) No liquid or loose ballast will be permitted.
- 9) A rear fuel cell with bladder is recommended.
- 10) Must have accessible fuel shut off valve clearly marked.
- 11) 70 inches, maximum – 56 inches, minimum wheelbase.
- 12) Roll cages must be attached to the frame with a minimum of 6 attachment points.
- 13) Helmet's must never extend above the roll cage. And must be 2 inches below the roll cage when seated in a normal position.
- 14) Cars must be equipped with nerf bars throughout the race. Period!
- 15) Bars must extend at least to the middle of the tire, but never beyond the outside of the tire.
- 16) All cars must be equipped with a firewall between the driver and the engine.
- 17) Minimum thickness specs are steel 24 gauge (0.0239 inches), Aluminum 0.050, Fiberglass or plastic 0.095 inches thick.
- 18) Floor pan must come to a point just rear of the front axle and tie rod to the front edge of the driver's seat.
- 19) Wing dimensions must be. TOP WING- Center of air foil cannot exceed 12 sq. ft. (1728 sq. in.) of surface area. Surface area is defined by the length x width of the flat plane of the largest projection of the of the center foil. TOP WING- must not extend beyond outside of the rear tire or behind the rear bumper. SIDE PANEL- Only two side panels are allowed. Maximum of 2" deep side panel, this is the protrusion of the stiffening members not including the struts (tubular or flat bar bracing). FRONT WING- Front Wings are optional.
- 20) Tires- OPEN

- 21) Seat belts must be 3" wide, 5-point approved racing harness, no more than 3 years old date stamp.
- 22) A helmet is required and must meet a minimum of SA-2015 standards appear to be in good condition.
- 23) Approved fire suit is MANDATORY; NOMEX underwear, head sock, and two-layer suit are highly recommended.
- 24) Fire resistant gloves, arm restraints and a "Hans" or similar neck restraint are MANDATORY.
- 25) Chain guard is MANDATORY.
- 26) Aluminum or carbon fiber full Containment racing seat is MANDATORY.
  
- 27) If you are unable to complete the rest of the night in your primary car, you CAN NOT leave to get another car. Your car is subject to inspection at any given time at track request. If car fails inspection, you and your car will not be allowed to compete, and no points will be collected.
  
- 28) If there is a spec that you are unsure of, please do not assume that it will be acceptable or legal. If you have questions about any of the rules or statements, please contact the Board of Directors.