

# GO KART RULES

**Voted 02/05/2026**

If the rule doesn't say you can, the default is you can't, unless approved by the Board of Directors and voted on by the class.

1) ALL CLASSES:

- A) Frames must be minimum of 1-inch round tubing.
- B) Minimum standard for roll cage: 1 inch .063 chrome molly or 1 inch .083 seamless tubing. Nose hoop must protect legs. Top of roll bar must extend a minimum of 2 inches above driver's helmet; **THIS RULE WILL BE STRICTLY ENFORCED!** Minimum 4-point roll bar required. Floating roll cages are allowed but must be securely fastened with chain or grade 5 or better bolts in at least four spots. Exception is flat karts in fart kart class only. For the 2028-2029 Race season, all Flat karts will be required to have a cage Home built karts are allowed if all safety rules are met.
- C) Nerf bars are mandatory and are not to extend beyond outer edge of tires by more than 1 inch unless tire is covered.
- D) Must have full floorboard under driver, extending 6 inches past drivers' feet.
- E) Axles must be solid mount. No springs, coils, shocks or suspension systems allowed.
- F) Front and rear bumpers must not extend beyond outer edge of tire
- G) Door bars are required and must open from the rear.
- H) No sharp or protruding objects on any part of the kart
- I) Numbers must be identifiable from left and right side of kart, and visible from the scoring tower. Numbers should be 6 inches tall. Numbers not legible will not be scored. **NO EXCEPTIONS!**
- J) Must have a positive throttle return spring.
- K) Must have a fuel shut off, from the tank to the engine.
- L) Must have engine shut off switch in driver's compartment and a secondary kill easily accessible by race officials.
- M) Belt or chain-drive only, no driven clutches or direct drives.
- N) Must have chain or belt guards from center line of sprockets.
- O) Must always have a rear brake in good working condition. Hydraulic Brakes are recommended in all classes and mandatory in MODS, 125's, 500's Fart Karts, and 270 Micro.
- P) Tire size to be no more than 10 inches wide.
- Q) Center of bumper must be 2 to 6 inches above racing surface. Recommend bumper to extend to outer edge of tire.
- R) **1 way receiver is REQUIRED!** Communication from the race director will aid in the direction of the race, including but not limited to safety and resetting the race lineup prior to any restart.
- S) Transponders as required by race officials. When required transponders are to be mounted to the steering post. No exceptions.

- T) No class jumping for seat time. If you are registered in a lower class and race competitively in a faster class, you will not be able to return to the lower class.
- U) Any weights added to the kart must be painted white, display the Kart number and be securely fastened to the kart.
- V) SRSCA service hours should be completed by the driver of the kart, unless exception approved by the board.
- W) All SRSCA general rules and procedures apply to all Kart classes

2) SAFETY EQUIPMENT AND INSPECTIONS - ALL CLASSES:

- A) 5-point harness required, 3 year date stamp recommended.
- B) Driver must have neck brace.
- C) SA2005 helmet or equivalent required. Must have face shield or goggles.
- D) Roll bar around driver must be padded.
- E) Racing approved wrist restraints are required and must be sufficient to keep arms and hands inside the cage of the kart.
- F) Gloves required
- G) Racing suit required. Fire suit and fire proof gloves highly recommended. You are ultimately responsible for you and your child's safety.
- H) Only track officials allowed on track during races. Violators are subject to ejection or disqualification
- I) Karts will be inspected with the following safety list. Failure to fix items may result in suspension of kart.

- |   |   |
|---|---|
| <input type="checkbox"/> Helmet – fit/condition                 | <input type="checkbox"/> Spindles – cotter Keyed or lock nuts |
| <input type="checkbox"/> Neck brace                             | <input type="checkbox"/> Roll Cage – condition/mounts         |
| <input type="checkbox"/> Driving suit                           | <input type="checkbox"/> Frame, Nerf bars, and bumpers        |
| <input type="checkbox"/> Gloves                                 | <input type="checkbox"/> Brakes                               |
| <input type="checkbox"/> Shoes                                  | <input type="checkbox"/> Steering link, lock nuts             |
| <input type="checkbox"/> Wrist restraints                       | <input type="checkbox"/> Kill switch                          |
| <input type="checkbox"/> Seat belt & harness-mounting/condition | <input type="checkbox"/> Floor pan condition                  |
| <input type="checkbox"/> Seat – condition/mounting              | <input type="checkbox"/> Number/letter – size/location        |
| <input type="checkbox"/> Steering wheel – securely mounted      | <input type="checkbox"/> Body and wing mounting               |
| <input type="checkbox"/> Protruding objects                     | <input type="checkbox"/> Chain Guard                          |
| <input type="checkbox"/> Axle protrusion                        | <input type="checkbox"/> General condition                    |
| <input type="checkbox"/> Fuel line - Location/condition         | <input type="checkbox"/> Fuel shut off                        |

**Any official is permitted to remove karts from track due to unsafe conditions to driver or other karts**

**TRACK OFFICIALS' DECISION IS FINAL**

3) BEGINNER CLASS:

- A) Drivers must be 5 years old; any exceptions must be approved by the Board of Directors and officials prior to race day.
- B) To keep the class competitive, if driving ability is shown to exceed the general ability of the class, drivers may be asked to move up a class at the discretion of the Board of Directors.
- C) Engine must be stock, 6.5 hp max horsepower/212cc yard equipment type, no blue printing. Absolutely no modification other than removing the governor. No racing engines. No exceptions!
- D) No restrictor plate required.
- E) Pump gas only. No additives.
- F) Muffler has to be stock to model of engine. No hollowing out muffler. No headers.
- G) Carburetors are stock to model of engine. No slide carburetors.
- H) Air filter and intake system is to be stock to engine used.
- I) Stock ignition only. No timing adjustments allowed.
- J) Stock cast iron flywheel only. No cutting or drilling on fly wheel.
- K) Minimum weight 245 lbs. with driver.
- L) All tire brands allowed.
- M) Drum/shoe style centrifugal type clutch only. no driven clutches or direct drives.

4) MOD (INTERMEDIATE/EXPERT) CLASS:

- A) Driver must be a minimum of 8 years old; any exceptions must be approved by the Board of Directors and officials prior to race day.
- B) Engine must be 6.5 hp/212cc yard equipment type, profile air cooled engine. Racing engines are allowed in this class.
- C) Racing fuel is allowed. No alcohol allowed.
- D) Headers and pipes are allowed maximum length 24 inches, must conform to profile of kart.
- E) Slide carburetors are allowed. Jetting changes are allowed.
- F) Minimum weight 300 lbs. with driver and equipment.

- G) Centrifugal, drum or disk type clutches are allowed. no driven clutches or direct drives.
- H) Billet flywheels Allowed. No Cutting or drilling on flywheel.
- I) Timing Adjustments allowed.
- J) Aftermarket air filter and adapter are allowed.

5) 125 OUTLAW:

- A) Drivers must be 10 – 18 years old. All drivers must be Board of Directors approved.
- B) Engine must be approved 2 stroke up to 125cc dirt bike engine. Must be stock stroke, maximum .080 over bore allowed.
- C) Stock OEM heads, may be milled, combustion area must remain stock.
- D) Cylinder and case may be ported.
- E) Kick starter may be removed and plugged.
- F) Must use stock, dirt bike type, up to 38mm carburetor. No modifications allowed. Carburetors may be interchanged among manufacturers.
- G) After market reeds/reed assemblies and spacers allowed.
- H) Must have complete and operable OEM transmission and clutch. No clutch conversions.
- I) PVL ignition is the only approved aftermarket ignition.
- J) Pipes and silencers must be Board of Directors approved and securely mounted within profile of kart.
- K) No lightening of any internal components.
- L) No decking the cylinder or block, no cylinder spacers or multiple gaskets allowed.
- M) No special factory parts allowed. All parts must be readily available to the average consumer.
- N) No welding/cutting/reshaping of cases.
- O) Minimum weight is 350 lbs., with driver
- P) Board of Directors approved tire.

6) 500 OUTLAW:

- A) Drivers must be at least 16 years old. All drivers must be Board of Directors approved.
- B) Engines must be approved, 2 stroke minimum 400cc, maximum 500cc plus .080 overbore, with stock stroke.
- C) Stock head may be milled and have water outlets welded.
- D) Minimum weight is 475 lbs., with driver.

E) All other applicable 125 outlaw rules apply.

7) FART KARTS:

THIS CLASS IS MEANT TO BE A FUN AND COMPETITIVE CLASS; RULES MAY BE ADJUSTED AS NEEDED

- A) Caged karts are highly recommended **cages will be required on all karts during the 2028-2029 race season**- Flat karts included, wings allowed on caged karts. Flat karts are allowed for the 2026-2027 season. If flat kart is used, no driver restraints are to be used.
- B) Drivers must be minimum 14 years of age as of date of race.
- C) Minimum weight of 400 lbs. with driver.
- D) Engine must be maximum 6.5 hp/212cc profile yard equipment type, air cooled engine.
- E) Headers or pipes are allowed. Maximum length 24 inches. Must conform to profile of kart.
- F) Carburetor modifications are allowed.
- G) Aftermarket air filter and adapter allowed.
- H) Pump gas only. No additives, No racing fuel, no alcohol allowed.
- I) All tire brands are allowed.
- J) Drum, shoe, and disc style centrifugal type clutch only. No driven clutches or direct drives.
- K) Billet flywheels and timing adjustments allowed.